

T350AA 0278xxx

Gumex, spol.s r.o.

Hot water & steam

ALFAGOMMA

mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
13	1/2	23	0,91	6	90				0,370	0,250
16	5/8	26	1,02	6	90				0,420	0,285
19	3/4	29	1,14	6	90				0,470	0,320
25	1	35	1,38	6	90				0,580	0,390
30	1 3/16	44	1,73	6	90				0,900	0,605
32	1 1/4	46	1,81	6	90				0,950	0,640
38	1 1/2	52	2,05	6	90				1,100	0,740
40	1 9/16	54	2,13	6	90				1,150	0,775
51	2	67	2,64	6	90				1,700	1,145
NA		LA	NEU	EMEA	SA	AP	AU			

**350AA****Steam 6 bar (90 psi)****hot water 15 bar (225 psi)****Tube:** Black conductive EPDM**Reinforcement:** High tensile textile cords**Cover:** Black conductive EPDM - heat, abrasion and ozone resistant**Use:** Saturated steam and hot water delivery in general industrial applications**Safety factor:** Water 4:1 - Steam 10:1**Temperature:** Water -40 °C +120 °C (-40 °F +248 °F)

Steam +165 °C (+330 °F)