

## // 714HA



### Drill cutting suction 5 bar (75 psi) - Corrugated

**Tube:** red NR - abrasion resistant.

**Reinforcement:** high tensile textile cords with embedded steel helix wire - antistatic wire.

**Cover:** black conductive SBR/NR - abrasion and ozone resistant.

**Application:** bulk material suction and delivery.  
Specially designed for drill cutting suction in mobile drilling rigs.  
Corrugated construction for maximum flexibility.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		↷		↯	↯	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	63,00	2,48	5	75	15	225	127,0	5,00	100	1,190	0,80
63,0	2 1/2"	77,00	3,03	5	75	15	225	157,0	6,18	90	1,860	1,26
76,0	3"	92,00	3,62	5	75	15	225	190,0	7,48	90	2,560	1,73
102,0	4"	119,00	4,69	5	75	15	225	255,0	10,04	90	3,580	2,41
115,0	4 1/2"	129,00	5,08	5	75	15	225	287,0	11,30	90	4,070	2,74
127,0	5"	141,00	5,55	5	75	15	225	318,0	12,52	80	4,710	3,17
152,0	6"	166,00	6,54	5	75	15	225	380,0	14,96	80	5,580	3,76