

## ALFAJET 210 1SN – hydraulická hadice, 210bar, -40 °C/+155 °C

### // ALFAJET 210



**Tube:** oil, detergents and hot water resistant synthetic rubber.

**Reinforcement:** one high tensile steel braid.

**Cover:** smooth. Abrasion, ozone and hydrocarbon resistant blue synthetic rubber, pin-pricked. Black cover also available.

**Application:** high pressure power cleaners. Specially designed for hot water applications. Not recommended for steam service.

**Length:** random

Item Code	↔ ⊙ ↔			↔ ⊙ ↔		⊙		⊙		⌒		⊞	
	Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft
1000192	04	6,0	1/4"	12,10	0,48	21,0	3000	84,0	12000	50,0	1,97	0,161	0,11
1000185	05	8,0	5/16"	14,10	0,56	21,0	3000	84,0	12000	60,0	2,36	0,184	0,13
1000098	06	10,0	3/8"	15,60	0,61	21,0	3000	73,0	10588	65,0	2,56	0,250	0,17
1000166	08	13,0	1/2"	19,50	0,77	21,0	3000	73,0	10588	90,0	3,54	0,359	0,25