

# GUMEX

// 350AA



**Steam 6 bar (90 psi) - Hot water 15 bar (225 psi)**

**Tube:** black conductive EPDM.

**Reinforcement:** high tensile textile cords.

**Cover:** black conductive EPDM - heat, abrasion and ozone resistant.

**Application:** saturated steam and hot water delivery in general industrial applications.

**Constant operation:** water -40 °C +120 °C (-40 °F +248 °F)  
steam +165 °C (+330 °F)

↔		↔		↙		↘		∩		⌋⌌	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	23,00	0,91	6	90	60	900				0,370	0,25
16,0	5/8"	26,00	1,02	6	90	60	900				0,430	0,29
19,0	3/4"	29,00	1,14	6	90	60	900				0,470	0,32
25,0	1"	35,00	1,38	6	90	60	900				0,590	0,40
30,0	1 3/16"	44,00	1,73	6	90	60	900				0,910	0,62
32,0	1 1/4"	46,00	1,81	6	90	60	900				0,950	0,64
38,0	1 1/2"	52,00	2,05	6	90	60	900				1,110	0,75
40,0	1 9/16"	54,00	2,13	6	90	60	900				1,160	0,78
51,0	2"	67,00	2,64	6	90	60	900				1,710	1,15