

		SCHEDA DATI TECNICI E CARATTERISTICHE	
TRADE NAME T130 EP-INT		COMPOSITION EPDM-EVA (SULFUR FREE)	
CELLULAR STRUCTURE		CLOSED CELL SPONGE RUBBER	
COLOR		BLACK	
HARDNESS	SHORE 00	60±10	
DENSITY (Kg/m³)	ISO 845	120 ± 20	
COMPRESSION DEFLECTION	ISO 3386 50% (kPa)	120 ± 40	
COMPRESSION DEFLECTION	ISO 3386 25% (kPa)	50 ± 15	
WATER ABSORPTION	ISO 6916	< 5 %	
ELONGATION AT BREAK	ISO 1798	≥ 400 %	
TENSILE STRENGTH	ISO 1798	≥ 600 kPa	
TEMPERATURE RANGE	CONSTANT	- 30 °C / + 80° C	
	INTERMITTENT	MAX + 100°C	
RESISTANCE	AIR + U.V.	EXCELLENT	
	FIRE, FMVSS 302 4mm	<100mm/min	
	OZONE (ISO 1431-1)	NO BREAK	
	OIL	NOT RECOMMENDED	
	ACIDS	GOOD	
ENVIRONMENTAL PROTECTION		CFC & HCFC FREE	
RECYCLING		PUO' ESSERE RICICLATO	