

// ALFAOIL EN 10 GG - 6J511 EN B **NEW**



Fuel-oil S&D 10 bar (150 psi) - Standard duty EN 13765 Type 2

Inner wire: galvanised steel wire.

Tube: polypropylene film.

Cover: grey PVC coated fabric with helicoidal blue stripe-white letters.

Outer wire: galvanised steel wire.

Application: fuel and oil suction and delivery.

Specially designed for tank truck applications.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

Electrical conductivity: ensured by the two wires in contact with fittings.

Electrical resistance: $\leq 2,5 \Omega/m$ up to DN 50 mm (2")

$\leq 1,0 \Omega/m$ over DN 50 mm (2")

Item Code	Product Code	ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)	Length (m)
2016457	6J511ENB025376WGU	25,0	1"	37,0	1,46	10	150	40	600	125	4,92	90,00	1,120	0,76	30,000
2017316	6J511ENB040536WGU	40,0	1 9/16"	53,0	2,09	10	150	40	600	150	5,91	90,00	1,720	1,16	30,000
2016459	6J511ENB050646WGU	50,0	2"	64,0	2,52	10	150	40	600	200	7,87	90,00	1,820	1,23	30,000
2017318	6J511ENB065776WGU	65,0	2 9/16"	77,0	3,03	10	150	40	600	200	7,87	90,00	1,920	1,30	30,000
2017291	6J511ENB080936WGU	80,0	3 1/8"	93,0	3,66	10	150	40	600	300	11,81	90,00	2,700	1,82	30,000
2016946	6J511ENB100186WGU	100,0	4"	118,0	4,65	10	150	40	600	400	15,75	90,00	4,200	2,83	30,000