

Hydraulická hadice – Flexopak 2SC

// FLEXOPAK 2SC



EN 857 2SC - ISO 11237

Tube: oil resistant synthetic rubber.

Reinforcement: two high tensile steel braids.

Cover: abrasion, ozone and hydrocarbon resistant synthetic rubber.

Application: high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.

Temperature: -40 °C +100 °C (-40 °F +212 °F)

air max T = +70 °C (+160 °F)

Length: random

| Item Code | ID (Dash) | ID (mm) | ID (in) | OD (mm) | OD (in) | WP (Mpa) | WP (psi) | BP (Mpa) | BP (psi) | BR (mm) | BR (in) | Weight (kg/m) | Weight (lb/ft) |
|-----------|-----------|---------|---------|---------|---------|----------|----------|----------|----------|---------|---------|---------------|----------------|
| 1000365 | 4 | 6,0 | 1/4" | 13,0 | 0,51 | 40,0 | 5850 | 160,0 | 23200 | 75 | 2,95 | 0,255 | 0,18 |
| 1000366 | 5 | 8,0 | 5/16" | 14,7 | 0,58 | 35,0 | 5000 | 140,0 | 20000 | 85 | 3,35 | 0,300 | 0,21 |
| 1000367 | 6 | 10,0 | 3/8" | 16,5 | 0,65 | 33,0 | 4800 | 132,0 | 19200 | 90 | 3,54 | 0,370 | 0,25 |
| 1000368 | 8 | 13,0 | 1/2" | 19,9 | 0,78 | 27,5 | 4000 | 110,0 | 16000 | 130 | 5,12 | 0,470 | 0,32 |
| 1000369 | 10 | 16,0 | 5/8" | 23,4 | 0,92 | 25,0 | 3630 | 100,0 | 14500 | 170 | 6,69 | 0,596 | 0,41 |
| 1000370 | 12 | 19,0 | 3/4" | 27,9 | 1,10 | 21,5 | 3120 | 86,0 | 12500 | 200 | 7,87 | 0,789 | 0,54 |
| 1000371 | 16 | 25,0 | 1" | 34,9 | 1,37 | 16,5 | 2400 | 66,0 | 9600 | 250 | 9,84 | 1,155 | 0,78 |